

| Trade Names and Metal Construction                              | Cross Section View | Methods of Attachment (Cross Section View) | Approx. Max. Curt. Wght. per foot of Track (lbs.)<br>**** | Maximum Track Length (Bi-parting)  | Carrier Spacing                               | Maximum Span Between Attachments  |  |
|---|--------------------|--|---|--|---|---|--|
|   |                    |  |   |  |   | Ceiling Mount   | Track Suspension                       |
| <b>SILENT STEEL®</b><br>Steel or Aluminum Track                 |                    |  | 20<br>25<br>30<br>50<br>50<br>30                          | Any length<br>Any length<br>Any length<br>Any length<br>Any length<br>Any length | 12"<br>12"<br>12"<br>12"<br>12"<br>12"        | --<br>--<br>--<br>--<br>--<br>--  | 7'<br>7'<br>7'<br>7'<br>7'<br>7'       |
| <b>BESTEEL®</b><br><b>FENESTEEL®</b><br>Steel or Aluminum Track |                    |  | 10<br>13<br>15<br>10<br>10<br>13<br>15                    | 36'<br>45'<br>45'<br>36'<br>Any length<br>Any length<br>Any length               | 12"<br>12"<br>12"<br>12"<br>12"<br>12"<br>12" | 18" ***<br>18" ***<br>18" ***<br>18" ***<br>18" ***<br>18" ***<br>18" *** | 6'<br>6'<br>6'<br>6'<br>6'<br>6'<br>6' |
| <b>PATRIARC®</b><br>Aluminum Track<br>(can be curved)           |                    |  | *<br>30<br>30   | Any length<br>Any length<br>Any length   | 12"<br>12"<br>12"                             | 5'<br>5'<br>5'  | 5'<br>5'<br>5'                         |
| <b>CURVIT-SURE®</b><br>Aluminum Track<br>(can be curved)        |                    |  | *<br>*<br>15<br>15<br>15                                  | 60' (No.350)<br>50' (No.340)<br>60'<br>Any length<br>Any length                  | 12"<br>12"<br>12"<br>12"<br>12"               | 5'<br>5'<br>5'<br>5'<br>5'  | 5'<br>5'<br>5'<br>5'<br>5'             |
| <b>TRIPL-I-TRAC®</b><br>Aluminum Track<br>(can be curved)       |                    |  | *<br>15<br>15   | 75'<br>75'<br>Any length   | 12"<br>12"<br>12"                             | 6'<br>6'<br>6'  | 6'<br>6'<br>6'                         |
| <b>RIG-I-FLEX®</b><br>Aluminum Track<br>(can be curved)         |                    |  | *<br>15<br>15   | 60'<br>60'<br>Any length   | 12"<br>12"<br>12"                             | 5'<br>5'<br>5'  | 4'<br>4'<br>4'                         |
| <b>FLEX-I-TRAC®</b><br>Aluminum Track<br>(can be curved)        |                    |  | 6.5<br>13<br>13   | Any length<br>Any length<br>Any length   | 12"<br>12"<br>12"                             | 5'<br>5'<br>5'  | 4'<br>4'<br>4'                         |
| <b>TRAK-EZE®</b><br>Aluminum Track                              |                    |  | 13<br>13  | 26'<br>26'   | 6"<br>12"                                     | 4'<br>4'  | 4'<br>4'                               |
| <b>MOTO-TRAC®</b><br>Motorized Aluminum Track                   |                    |  | 4   | 25'  | 6"  | 12"   | 4'                                     |
| <b>VERS-UTIL®</b><br>Aluminum Track<br>(can be curved)          |                    |  | 4   | 40'  | 6"  | 12"   | 4'                                     |
| <b>SPECIFINE®</b><br>Aluminum Track                             |                    |  | 4   | 20'  | 6"  | 12"***  | 4'                                     |

\* An accurate figure for the Approximate Maximum Curtain Weight Per Foot of Track cannot be established for cord-operated curved tracks due to immeasurability of certain variable factors.

\*\* Data in Tables A and B are based on average track length for individual track models.

\*\*\* This figure is based on direct attachment of track channel to ceiling.

\*\*\*\* Based on standard carrier spacing.

